

### LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) An actuator connectable to and for adjusting a device, wherein the actuator comprises:

a housing having a longitudinal passage extending between a first end and a second end of the housing and defining an opening at or adjacent to the second end;

a spindle supported in the housing and movable longitudinally in the housing passage, the spindle having two oppositely handed, ~~longitudinally spaced~~ threaded portions longitudinally spaced from each other with respect to an axis the spindle rotates about of which a first threaded portion is nearer to the first end and a second threaded portion is nearer to the second end;

a first threaded nut fixed relative to the housing and threadedly engaged with the first threaded portion of the spindle;

a handle rotatably mounted at the first end of the housing, the handle being coupled to the spindle for rotating the spindle in the first nut and thereby moving the spindle longitudinally relative to the first nut and the housing;

a second nut fixed against rotation relative to the housing and threadedly engaged with the second threaded portion of the spindle, whereby in response to rotation of the spindle by the handle the second nut is movable longitudinally in the housing passage relative to the spindle, in the same direction as movement of the spindle relative to the housing; and

connecting means on or of the second nut and ~~connectable~~ configured to be connected, through the opening defined by the housing, to a device to be adjusted by the actuator;

wherein the spindle is ~~rotatable~~ configured to rotate by the handle for adjusting the ~~adjustable~~ device by longitudinal movement in the same direction of the spindle relative to the housing and of the second nut relative to the spindle.

2. (Currently Amended) An actuator connectable to and for adjusting a device, wherein the actuator-comprises:

a housing having a longitudinal passage extending between a first end and a second end of the housing and defining an opening at or adjacent to the second end;

a spindle supported in the housing and movable longitudinally in the housing passage, the spindle having two oppositely handed, longitudinally spaced threaded portions of which a first threaded portion is nearer to the first end and a second threaded portion is nearer to the second end;

a first threaded nut fixed relative to the housing and threadedly engaged with the first threaded portion of the spindle;

a handle rotatably mounted at the first end of the housing, the handle being coupled to the spindle for rotating the spindle in the first nut and thereby moving the spindle longitudinally relative to the first nut and the housing;

a second nut fixed against rotation relative to the housing and threadedly engaged with the second threaded portion of the spindle, whereby in response to rotation of the spindle by the handle the second nut is movable longitudinally in the housing passage relative to the spindle, in the same direction as movement of the spindle relative to the housing; and

connecting means on or of the second nut and ~~connectable~~ configured to connect, through the opening defined by the housing, to a device to be adjusted by the actuator;

wherein the spindle is rotatable by the handle for adjusting the ~~adjustable~~ device by longitudinal movement in the same direction of the spindle relative to the housing and of the second nut relative to the spindle;

wherein the actuator further comprises:

an opening formed in the second nut and configured for receiving and securing an end of a cable of a Bowden cable system and thereby comprising the connecting means; and

the housing at the second end having an engagement member for fixing a sleeve of the Bowden cable system;

wherein the spindle is operable for moving the cable longitudinally through the sleeve for adjusting the adjustable device to which the other end of the Bowden cable system is connected.

3. (Currently Amended) The actuator of claim 1, wherein the actuator is adapted for connection to the device by a direct coupling between the second nut and the device, by a projection which extends laterally of the second nut, through the opening defined by the housing, with that opening being in the form of an elongate slot extending longitudinally along the housing at the second end.

4. (Withdrawn) The actuator of claim 3, wherein the coupling is provided by a respective said projection projecting through a respective said elongate slot at each of opposed sides of the second nut and housing.

5. (Withdrawn) The actuator of claim 3, wherein the projection extends from the second nut and comprises the connecting means.

6. (Canceled).

7. (Original) The actuator of claim 1, wherein each threaded portion has a thread of a substantially common pitch.

8. (Currently Amended) The actuator of claim 1, wherein the handle is mounted on the housing and held thereon against longitudinal movement relative to the housing, and wherein the a

coupling between the handle and the spindle enables the spindle to adjust longitudinally relative to the handle as the spindle moves longitudinally with respect to the housing.

9. (Currently Amended) The actuator of claim 8, wherein an end portion of the spindle at the first end of the housing is ~~movable~~ configured to move longitudinally within a sleeve defined by the handle, and wherein there is a key and keyway or splined coupling between the sleeve of the handle and the spindle.

10. (Original) The actuator of claim 1, wherein the first nut is held against rotation by a key and keyway engagement with the housing.

11. (Currently Amended) The actuator of claim 1 ~~or claim 10~~, wherein the first nut is held against movement longitudinally of the housing by being located between a shoulder and at least one tab, and wherein the shoulder is defined by the housing and faces towards the first end and the at least one tab is formed integrally with the housing and protruding resiliently into the passage.

12. (Original) The actuator of claim 1, wherein the second nut has first and second longitudinally adjacent sections, of which the first section comprises an internally threaded sleeve by which the second nut is engaged with the second threaded portion of the spindle and the second section extends longitudinally beyond the spindle from the first section, towards the second end of the housing.

13. (Original) The actuator of claim 2, wherein the second nut has first and second longitudinally adjacent sections, of which the first section comprises an internally threaded sleeve by which the second nut is engaged with the second threaded portion of the spindle and the second section

extends longitudinally beyond the spindle from the first section, towards the second end of the housing;  
and

wherein the opening comprising the connecting means is formed in and opens laterally of the second section and the second section further defines a radial slot which extends from the lateral opening towards the second end of the housing whereby, with the nipple of the cable of the Bowden system received in the lateral opening, the cable can be adjusted so as to extend longitudinally from the second nut.

14. (Original) The actuator of claim 13, wherein the housing defines a side opening communicating with the passage and a slot extending from the side opening to the second end whereby a cable adjusted so as to extend longitudinally from the second nut also is able to be adjusted to extend through the second end of the housing.

15. (Original) The actuator of claim 1, wherein the second nut is of substantially circular cross-section and has at least one radial projection which is slidable along a longitudinal slot defined by the housing along a part of the passage along which the second nut is movable relative to the spindle.

16. (Original) The actuator of claim 2, wherein the engagement member at the second end of the housing is a sub-housing adapted to receive therein a suitably shaped termination of the sleeve of the Bowden system.

17. (Currently Amended) The actuator of claim 16, wherein the sub-housing has a part cylindrical peripheral wall which defines a lateral opening through which at least part of the terminator is ~~receivable~~ configured to receive, and an inwardly extending flange or bead at an edge of the wall

remote from the housing for retaining the termination from longitudinal disengagement from the actuator.

18. (Currently Amended) The actuator of claim 1, wherein the spindle has an unthreaded part of its length between adjacent ends to the threads of the first and second~~section~~ threaded portions, with said unthreaded part having abutment means for providing a sharply defined stop when the spindle and the second nut are moved towards the second stop to respective limiting positions.

19. (Currently Amended) The actuator of claim ~~8~~ 18, wherein said abutment means is provided by a lateral tab projecting from the spindle, with the lateral tab having a leading face in the direction of rotation of the spindle for movement towards the second end, and the abutment means is adapted to stop rotation of the spindle by said abutment face abutting a surface defined by the housing.

20. (New) The actuator of claim 1, wherein the first and second nuts are internally threaded and have no external threads.

21. (New) The actuator of claim 1, wherein the first and second nuts have substantially the same diameter.